

## CHARON-AXP/400, /2000, and /4100 for Windows

Product version 4.8

Document: 60-15-085-002

### DESCRIPTION

Stromasys **CHARON-AXP/400, CHARON-AXP/2000, and CHARON-AXP/4100** are members of CHARON-AXP cross-platform hardware virtualization product family. They are designed to replace the following DEC AlphaServer computer systems by its virtual equivalent running on an x86-64 compatible standard computer system:

CHARON-AXP product	Hardware to replace
<b>CHARON-AXP/400</b>	AlphaServer 400, 1000, 1000A
<b>CHARON-AXP/2000</b>	AlphaServer 800, 1200, 2000, 4000 (and also 400, 1000, 1000A)
<b>CHARON-AXP/4100</b>	AlphaServer 2100, 4100 (and also 400, 1000, 1000A, 800, 1200, 2000, 4000)

Most of the original Alpha-hardware is virtualized by CHARON-AXP. It runs the original Alpha binary code, including operating systems OpenVMS and Tru64 UNIX, the layered products, and applications, which remaining working as always. Very few changes might be required to the original software (operating system, layered products, or applications). The Tru64 kernel might require a rebuild.

### NETWORK

CHARON-AXP virtualizes the 10/100 Mbps Ethernet controllers from DEC 21x4x and Intel 8255x families, ensuring support of any AlphaServer installation. Any protocol that ran over a physical Alpha Ethernet link (DECnet, TCP/IP, and LAT) will run over a virtualized CHARON link. The CHARON network adapter is recognized by the operating system which assumes it will run at 10/100Mbps, but since it's virtualized, it may exceed that speed when connected to a 1Gbps / 10Gbps adapter in the host system. The network performance also depends on design limitations of the guest VMS/Tru64 OS.

### STORAGE

CHARON-AXP provides support for Alpha disk, tape, and CD/DVD storage devices via virtual KZPBA SCSI and KGPSA FC adapters, translating them into any modern technology (SCSI, SATA, SAS) by means of virtual disk images on a Windows filesystem or physical LUNs attached locally or remotely by iSCSI, SAN, or NAS.

### PCI PASSTHROUGH

Emulex FC adapters compatible with original AlphaServer hardware (FC KGPSA), serial line PBXDA adapter, and FDDI DEPFA adapter can be used by CHARON-AXP to provide direct access to SAN infrastructure, serial lines, and FDDI network, equivalent to physical Alpha access. Using PCI Passthrough method allows gaining up to 50% performance improvement on the disk I/O compared to using virtual storage controllers. It is recommended for high performance configurations with access to SAN infrastructure.

### HOST SYSTEM REQUIREMENTS

A physical system or virtual appliance with multi core CPUs (Intel Xeon v4 E3, E5, and E7 CPUs with a clock frequency of 3GHz and above are recommended), dedicated Ethernet adapters, an optional USB port for the license key and enough disk space to keep the OpenVMS or Tru64 data. For every emulated AXP CPU, CHARON must have exclusive access to at least 2 CPU cores on the host system. CHARON-AXP requires a minimum of 2 GB host RAM (base) plus 2 GB in addition to the amount of AXP RAM per emulated AXP.

### PERFORMANCE

SPEC2000 test running on Tru64 5.1B on CHARON-AXP emulating AlphaServer 4100 delivers about **SPEC2000 INT 834** and **SPEC2000 FP 678 per CPU** on a desktop with Intel Core i7-4790K 4GHz CPU.

CHARON-AXP benefits from the newer, faster hardware, offering equal or better performance compared to most Alpha systems. The constant improvements Stromasys makes to the CHARON products, together with rapidly developing faster hardware, will further shift the balance in favor of cross-platform virtualization. Full SPEC2000 data for all physical Alpha systems can be accessed online at <https://www.spec.org/cpu2000/>

### SYSTEM MAINTENANCE

Once installed and configured, CHARON system will behave like the original Alpha system, and can be treated like Alpha. Guest OS and applications operating procedures will remain the same, and it's advised not to treat the system as a Windows box, despite the fact it runs on a Windows kernel. Hosting OS does not require maintenance or patching; it can be cut off the network completely.

### LICENSE PROTECTION

A valid license should be permanently available to CHARON. It can be represented by a local or network attached USB HASP license dongle, or a Software License. The license preserves customer specific parameters and allows remote electronic updates. USB dongle enables rapid change of host systems as the CHARON executable itself can be installed on multiple systems for disaster recovery purposes. License flexibility allows combining multiple instances of different CHARON products on a single host system.

### DISTRIBUTION

CHARON Release notes, User manuals and Software Product Descriptions are available for download from the Stromasys Product Documentation and Knowledge Base web pages. Downloading installation kits and patches requires a partner account or credentials provided by Stromasys on an individual basis.

### CHARON UTILITIES

CHARON-AXP on Windows is delivered with the **CHARON Virtual Machines Manager**, a single window application which consolidates all CHARON management tasks: creating and configuring CHARON instances, managing CHARON license, configuring hosting hardware resources for CHARON needs, etc. The following functional applications are invoked from CHARON VM manager:

- **HASP License Details** for viewing CHARON license(s)
- **License Update Tool** for updating CHARON license
- **Sentinel Admin Control Center** for license management
- **Network Control Center** for managing CHARON network drivers and settings
- **Device Check** for providing configuration assistance for directly connected host devices
- **Virtual Disk Tool** for creating empty disk image files (.vdisk)

The following command line utilities are also available:

- **Virtual Disk Tool** for creating empty disk image files (.vdisk)
- **MTD** for transferring data between physical tapes and CHARON tape container files, and converting virtual tape format between CHARON-AXP flavors

Stromasys **CHARON Guest Utilities for OpenVMS** version 6.1 and above are supplied on a disk image to provide the following functionality:

- **Tape Utilities Package** for manipulating virtual tape images and managing a virtual SCSI tape changer
- **VMS bypass driver** for emulating DU/DR/DG/DQ/DI disk devices
- **Power consumption optimization (IDLE) VMS utility** for implementing energy save mode when virtual AXP CPU is idle

## VIRTUALIZED HARDWARE

CHARON Product	CHARON-AXP/400		CHARON-AXP/2000 <sup>1)</sup>				CHARON-AXP/4100 <sup>2)</sup>	
Emulated hardware model	AlphaServer 400	AlphaServer 1000 / 1000A	AlphaServer 800	AlphaServer 1200	AlphaServer 2000	AlphaServer 4000	AlphaServer 2100	AlphaServer 4100
Alpha CPUs (base / maximum)	1 / 1	1 / 1	1 / 1	1 / 2	1 / 2	1 / 2	1 or 2 / 4	1 or 2 / 4
Emulated RAM	Up to 1GB	Up to 1 GB	Up to 8 GB	Up to 8 GB	Up to 2 GB	Up to 2 GB	Up to 32 GB	Up to 32 GB
Virtual PCI slots	3	3/7	4	6	3	16	3	8
Virtual CPU performance level	50%		Full (100%)				Full (100%)	
Storage adapter support	Emulated PCI SCSI KZPBA adapters (1 preloaded); emulated PCI FC KGPSA adapters; Up to 120 storage units (disks, tapes, and CD/DVD) supported simultaneously							
Disk storage support	<b>Virtual:</b> disk images on a local and remote Windows file system (.vdisk container files); <b>Logical:</b> iSCSI disks; SAN attached storage volumes (\\PhysicalDriveX and \\DevID devices) <b>Physical:</b> physically attached SCSI disks and partitions (original Alpha SCSI disks can be used)							
Tape storage support	Virtual tape images on a local and remote Windows file system (.vtape container files); physical SCSI tape drives (\\TapeX or \\SCSI devices)							
CDROM / Floppy disk support	Virtual CD/DVDs images (.iso container files); Physical CD/DVD drives (\\CdRomX devices) / Physical floppy drive 1.44 MB (\\A: device)							
Ethernet Network support	Emulated PCI DEC 21x4x adapters: DE435, DE450, DE500AA, and DE500BA (1 preloaded DEC TULIP 21040 for AS2x00); Emulated PCI Intel 82558 10/100 Mbps adapters: DE602 and DE602AA							
Fiber Channel/FDDI support	Direct connection to SAN with physical KGPSA or compatible FC EMULEX HBA adapters (up to 8 Gbps) in Passthrough mode; Direct connection to SAN with Windows supported FC HBA adapters in Presentation mode / Direct connection to FDDI network with physical DEFPDA adapters							
Console / Serial lines	OPA0 console attached to a Windows terminal emulator, a physical serial port (COMxx: device), or a TCP/IP socket / Emulated PCI serial line controller PBXDA (8 serial lines)							
Supported operating systems	OpenVMS 6.2-1H3 – OpenVMS 8.4; Digital UNIX 3.2 – 4.0E; Tru64 UNIX 4.0F – 5.1B (also known as: Compaq or HP Tru64 UNIX)							

<sup>1)</sup> CHARON-AXP/2000 also includes all Alpha hardware models emulated by CHARON-AXP/400

<sup>2)</sup> CHARON-AXP/4100 also includes all Alpha hardware models emulated by CHARON-AXP/400 and /2000

### Host system requirements

Host operating system	Microsoft Windows Server 2012 R2, Server 2008 R2 (Standard and Enterprise editions 64 bit) – please notice that only R2 revisions are supported; Microsoft Windows 7; 8.1, and 10 (Professional and Enterprise Editions 64 bit); on top of a physical host; or on VMware ESXi 5.5 or 6.x; or on Microsoft Hyper-V
Host CPU / RAM	Amount of host system CPU cores $\geq 2 * (\text{amount of emulated AXP CPU cores})$ ; Host RAM = 2 GB + ( 2 GB + AXP RAM ) per emulated AXP ) minimum
Recommended Hardware	HP ProLiant G9 servers; Intel Xeon v4 E3, E5 and E7 CPUs; Intel Core 7 <sup>th</sup> generation CPUs; CPU frequency 3 GHz and above

### Ordering information

CHARON Product	CHARON-AXP/400 (single CPU)	CHARON-AXP/2000 (single CPU)	CHARON-AXP/4100 (single CPU / dual CPU)
Perpetual license	CHAXP-616IP	CHAXP-626IP	CHAXP-606IP / CHAXP-806IP
Annual license	CHAXP-616IY	CHAXP-626IY	CHAXP-606IY / CHAXP-806IY
Annual GOLD Support (9*5)	CHAXP-616IU	CHAXP-626IU	CHAXP-606IU / CHAXP-806IU
Annual PLATINUM Support (24*7)	CHAXP-616IT	CHAXP-626IT	CHAXP-606IT / CHAXP-806IT
Backup license	CHAXP-616IK	CHAXP-626IK	CHAXP-606IK / CHAXP-806IK
Additional CPU	N/A	CHAXP-CPUIP	CHAXP-CPUIP

#### STROMASYS INC

Americas Region  
2840 Plaza Place  
Ste 450  
Raleigh, NC 27612  
United States of America  
Phone: +1 919 239 8450  
Fax: +1 919 239 8451  
us.sales@stromasys.com

#### STROMASYS SA

Europe, Middle East & Africa  
Avenue Louis-Casai 84  
5<sup>th</sup> Floor  
1216 Cointrin-Geneva  
Switzerland  
Phone: +41 22 794 1070  
Fax: +41 22 794 1073  
emea.sales@stromasys.com

#### STROMASYS ASIA PACIFIC LTD

Asia Pacific Region  
Room 1102, 11/F, Lee Garden One  
33 Hysan Avenue  
Causeway Bay, Hong Kong  
Hong Kong SAR of People's Republic of China  
Phone: +852 3959 8788  
Fax: +852 3959 8800  
apac.sales@stromasys.com



stromasys  
engineered solutions