

# CHARON-AXP/DS10, /DS20, /ES40, /GS80, /GS160, and /GS320 for Windows

Product version 4.8

Document: 60-15-086-002

## DESCRIPTION

Stromasys **CHARON-AXP/DS/ES/GS** are members of CHARON-AXP cross-platform hardware virtualization product family. They are designed to replace the following DEC AlphaServer computer systems:

CHARON-AXP product	Hardware to replace
CHARON-AXP/DS10	AlphaServer DS10, DS15
CHARON-AXP/DS20	AlphaServer DS20, DS25
CHARON-AXP/ES40	AlphaServer ES40, ES45, ES47
CHARON-AXP/GS80	AlphaServer GS80, GS60, ES80
CHARON-AXP/GS160	AlphaServer GS140, GS160
CHARON-AXP/GS320	AlphaServer GS320, GS1280

Most of the original Alpha hardware is virtualized by CHARON-AXP. It runs the original Alpha binary code, including operating systems OpenVMS and Tru64 UNIX, the layered products, and applications, which remaining working as always. Very few changes might be required to the original software (operating system, layered products, or applications). The Tru64 kernel might require a rebuild.

## NETWORK

CHARON-AXP virtualizes the 10/100 Mbps Ethernet controllers from DEC 21x4x and Intel 8255x families, ensuring support of any AlphaServer installation. Any protocol that ran over a physical Alpha Ethernet link (DECnet, TCP/IP, and LAT) will run over a virtualized CHARON link. The CHARON network adapter is recognized by the operating system which assumes it will run at 10/100Mbps, but since it's virtualized, it may exceed that speed when connected to a 1Gbps / 10Gbps adapter in the host system. The network performance also depends on design limitations of the guest VMS/Tru64 OS.

## STORAGE

CHARON-AXP provides support for Alpha disk, tape, and CD/DVD storage devices via virtual KZPBA SCSI and KGPSA FC adapters, translating them into any modern technology (SCSI, SATA, SAS) by means of virtual disk images on a Windows filesystem or physical LUNs attached locally or remotely by iSCSI, SAN, or NAS.

## PCI PASSTHROUGH

Emulex FC adapters compatible with original AlphaServer hardware (FC KGPSA), serial line PBXDA adapter, and FDDI DEPFA adapter can be used by CHARON-AXP to provide direct access to SAN infrastructure, serial lines, and FDDI network, equivalent to physical Alpha access. Using PCI Passthrough method allows gaining up to 50% performance improvement on the disk I/O compared to using virtual storage controllers. It is recommended for high performance configurations with access to SAN infrastructure.

## HOST SYSTEM REQUIREMENTS

A physical system or virtual appliance with multi core CPUs (Intel Xeon v4 E3, E5, and E7 CPUs with a clock frequency of 3GHz and above are recommended), dedicated Ethernet adapters, an optional USB port for the license key and enough disk space to keep the OpenVMS or Tru64 data. For every emulated AXP CPU, CHARON must have exclusive access to at least 2 CPU cores on the host system. CHARON-AXP requires a minimum of 2 GB host RAM (base) plus 2 GB in addition to the amount of AXP RAM per emulated AXP.

## PERFORMANCE

SPEC2000 test running on Tru64 5.1B on CHARON-AXP emulating AlphaServer ES45 delivers about **SPEC2000 INT 834** and **SPEC2000 FP 678 per CPU** on a desktop with Intel Core i7-4790K 4GHz CPU. CHARON-AXP benefits from the newer, faster hardware, offering equal

or better performance compared to most Alpha systems. The constant improvements Stromasys makes to the CHARON products, together with rapidly developing faster hardware, will further shift the balance in favor of cross-platform virtualization. Full SPEC2000 data for all physical Alpha systems can be accessed online at <https://www.spec.org/cpu2000/>

## SYSTEM MAINTENANCE

Once installed and configured, CHARON system will behave like the original Alpha system, and can be treated like Alpha. Guest OS and applications operating procedures will remain the same, and it's advised not to treat the system as a Windows box, despite the fact it runs on a Windows kernel. Hosting OS does not require maintenance or patching; it can be cut off the network completely.

## LICENSE PROTECTION

A valid license should be permanently available to CHARON. It can be represented by a local or network attached USB HASP license dongle, or a Software License. The license preserves customer specific parameters and allows remote electronic updates. USB dongle enables rapid change of host systems as the CHARON executable itself can be installed on multiple systems for disaster recovery purposes. License flexibility allows combining multiple instances of different CHARON products on a single host system.

## DISTRIBUTION

CHARON Release notes, User manuals and Software Product Descriptions are available for download from the Stromasys Product Documentation and Knowledge Base web pages. Downloading installation kits and patches requires a partner account or credentials provided by Stromasys on an individual basis.

## CHARON UTILITIES

CHARON-AXP on Windows is delivered with the **CHARON Virtual Machines Manager**, a single window application which consolidates all CHARON management tasks: creating and configuring CHARON instances, managing CHARON license, configuring hosting hardware resources for CHARON needs, etc. The following functional applications are invoked from CHARON VM manager:

- **HASP License Details** for viewing CHARON license(s)
- **License Update Tool** for updating CHARON license
- **Sentinel Admin Control Center** for license management
- **Network Control Center** for managing CHARON network drivers and settings
- **Device Check** for providing configuration assistance for directly connected host devices
- **Virtual Disk Tool** for creating empty disk image files (.vdisk)

The following command line utilities are also available:

- **Virtual Disk Tool** for creating empty disk image files (.vdisk)
- **MTD** for transferring data between physical tapes and CHARON tape container files, and converting virtual tape format between CHARON-AXP flavors

Stromasys **CHARON Guest Utilities for OpenVMS** version 6.1 and above are supplied on a disk image to provide the following functionality:

- **Tape Utilities Package** for manipulating virtual tape images and managing a virtual SCSI tape changer
- **VMS bypass driver** for emulating DU/DR/DG/DQ/DI disk devices
- **Power consumption optimization (IDLE) VMS utility** for implementing energy save mode when virtual AXP CPU is idle



## VIRTUALIZED HARDWARE

CHARON product	CHARON-AXP/DS10	CHARON-AXP/DS20	CHARON-AXP/ES40	CHARON-AXP/GS80	CHARON-AXP/GS160	CHARON-AXP/GS320
<b>Emulated AlphaServer model</b>	DS10, DS15	DS20, DS25	ES40, ES45, ES47	GS60, GS80, ES80	GS140, GS160	GS320, GS1280
<b>Alpha CPUs (base / maximum)</b>	1 / 1	1 / 2	2 / 4	4 / 8	8 / 16	16 / 32
<b>Emulated RAM</b>	Up to 32 GB	Up to 32 GB	Up to 32 GB	Up to 64 GB	Up to 128 GB	Up to 256 GB
<b>Available virtual PCI slots</b>	4	6	10	27	27	27
<b>Storage adapter support</b>	Emulated PCI SCSI KZPBA adapters (2 preloaded for DS20, DS25; 1 preloaded for GS series); Emulated PCI FC KGPSA adapters; up to 120 storage units (disks, tapes, and CD/DVD) supported simultaneously; Emulated Acer Labs 1543C IDE/ATAPI controller (1 preloaded; only virtual IDE CD/DVD devices)					
<b>Disk storage support</b>	Virtual disk images on a local and remote Windows file system (.vdisk container files); physical SCSI disks and partitions; iSCSI disks; SAN attached storage volumes (\\.\PhysicalDriveX devices)					
<b>Tape storage support</b>	Virtual tape images on a local and remote Windows file system (.vtape container files); physical SCSI tape drives (\\.\TapeX or \\.\SCSI devices)					
<b>CDROM / Floppy disk support</b>	Virtual CD/DVDs images (.iso container files); physical CD/DVD drives (\\.\CdRomX devices) / Physical floppy drive 1.44 MB (\\.\A: device)					
<b>Ethernet Network support</b>	Emulated PCI DEC 21x4x adapters: DE435, DE450, DE500AA, and DE500BA (2 DEC 21143 controllers preloaded for DS10, DS15; 1 preloaded for DS25); Emulated PCI Intel 82558 10/100 Mbps adapters: DE602 and DE602AA					
<b>Fiber Channel / FDDI support</b>	Direct connection to SAN with physical KGPSA or compatible FC EMULEX HBA adapters (up to 8 Gbps) in Passthrough mode; Direct connection to SAN with Windows supported FC HBA adapters in Presentation mode / Direct connection to FDDI network with physical DEFPA adapters					
<b>Console / Serial lines</b>	OPA0 console attached to a Windows terminal emulator, a physical serial port (COMxx: device), or a TCP/IP socket					
<b>Supported operating systems</b>	OpenVMS 7.1-2 – OpenVMS 8.4, Tru64 UNIX 4.0F – 5.1B (also known as: Compaq or HP Tru64 UNIX)			OpenVMS 7.2-1H1 – OpenVMS 8.4, Tru64 UNIX 4.0G – 5.1B (also known as: Compaq or HP Tru64 UNIX)		

## Host system requirements

<b>Host operating system</b>	Windows Server 2012 R2, 2008 R2 (Standard and Enterprise editions 64 bit) – please notice that only R2 revisions are supported; Microsoft Windows 7; 8.1, and 10 (Professional and Enterprise Editions 64 bit); on top of a physical host; or on VMware ESXi 5.5 or 6.x; or on Microsoft Hyper-V
<b>Host CPU/RAM</b>	Amount of host system CPU cores $\geq 2^*$ (amount of emulated AXP CPU cores); Host RAM = 2 GB + ( 2 GB + AXP RAM) per emulated AXP ) minimum
<b>Recommended Hardware</b>	HP ProLiant G9 servers; Intel Xeon v4 E3, E5 and E7 CPUs; Intel Core 7 <sup>th</sup> generation CPUs; CPU frequency 3 GHz and above

## Ordering information

<b>Perpetual license</b>	CHAXP-801IP	CHAXP-802IP	CHAXP-804IP	CHAXP-808IP	CHAXP-809IP	CHAXP-909IP
<b>Annual license</b>	CHAXP-801IY	CHAXP-802IY	CHAXP-804IY	CHAXP-808IY	CHAXP-809IY	CHAXP-909IY
<b>Annual GOLD Support (9*5)</b>	CHAXP-801IU	CHAXP-802IU	CHAXP-804IU	CHAXP-808IU	CHAXP-809IU	CHAXP-909IU
<b>Annual PLATINUM Support (24*7)</b>	CHAXP-801IT	CHAXP-802IT	CHAXP-804IT	CHAXP-808IT	CHAXP-809IT	CHAXP-909IT
<b>Backup license</b>	CHAXP-801IK	CHAXP-802IK	CHAXP-804IK	CHAXP-808IK	CHAXP-809IK	CHAXP-909IK
<b>Additional CPU</b>	N/A	CHAXP-CPUIP	CHAXP-CPUIP	CHAXP-CPUIP	CHAXP-CPUIP	CHAXP-CPUIP

### STROMASYS INC

Americas Region  
2840 Plaza Place  
Ste 450  
Raleigh, NC 27612  
United States of America  
Phone: +1 919 239 8450  
Fax: +1 919 239 8451  
us.sales@stromasys.com

### STROMASYS SA

Europe, Middle East & Africa  
Avenue Louis-Casai 84  
5<sup>th</sup> Floor  
1216 Cointrin-Geneva  
Switzerland  
Phone: +41 22 794 1070  
Fax: +41 22 794 1073  
emea.sales@stromasys.com

### STROMASYS ASIA PACIFIC LTD

Asia Pacific Region  
Room 1102, 11/F, Lee Garden One  
33 Hysan Avenue  
Causeway Bay, Hong Kong  
Hong Kong SAR of People's Republic of China  
Phone: +852 3959 8788  
Fax: +852 3959 8800  
apac.sales@stromasys.com



**stromasys**  
engineered solutions